



Standard Extra Wide Couplings are principally designed for joining large diameter pipes of size DN1000 and greater. The 300mm width of the coupling allows for greater tolerance in the cutting of the pipe ends as well as providing for greater movement of the pipe ends due to settlement or thermal movement.

Whilst generally used on pipes over DN1000 couplings are available to suit pipes from DN300.

These couplings, because of their extra width can also be used to repair pipes, which are cracked or have suffered local damage.

All couplings are manufactured to suit specific site requirements and can be produced in any diameter.

## Uses

- Connection of large diameter pipes.
- Repair of cracked or locally damaged pipes.
- Use where angular deflection at the joint is greater than that allowed by a Standard Coupling.

## EXTRA WIDE STANDARD COUPLINGS

REFERENCE NUMBER	SIZE RANGE (mm)	WIDTH (mm)	T (mm)
MSC 250W	225 - 250	300	10
MSC 275W	250 - 275	300	10
MSC 290W	265 - 290	300	10
MSC 310W	285 - 310	300	10
MSC 320W	290 - 320	300	10
MSC 335W	310 - 335	300	10
MSC 350W	325 - 350	300	10
MSC 360W	335 - 360	300	10
MSC 385W	355 - 385	300	10
MSC 410W	385 - 410	300	10
MSC 430W	400 - 430	300	10
MSC 445W	415 - 445	300	10
MSC 465W	435 - 465	300	10
MSC 490W	460 - 490	300	10
MSC 510W	480 - 510	300	10
MSC 525W	495 - 525	300	10
MSC 545W	515 - 545	300	10
MSC 560W	530 - 560	300	10
MSC 570W	540 - 570	300	10
MSC 580W	550 - 580	300	10
MSC 600W	570 - 600	300	10
MSC 620W	590 - 620	300	10

## EXTRA WIDE LARGE COUPLINGS

REFERENCE NUMBER	SIZE RANGE (mm)	WIDTH (mm)	T (mm)
MLC 600W	601 - 699	300	10
MLC 700W	700 - 799	300	10
MLC 800W	800 - 899	300	10
MLC 900W	900 - 999	300	10
MLC 1000W	1000 - 1099	300	10
MLC 1100W	1100 - 1199	300	10
MLC 1200W	1200 - 1299	300	10
MLC 1300W	1300 - 1399	300	10
MLC 1400W	1400 - 1499	300	10
MLC 1500W	1500 - 1599	300	10
MLC 1600W	1600 - 1699	300	10
MLC 1700W	1700 - 1799	300	10
MLC 1800W	1800 - 1899	300	10
MLC 1900W	1900 - 1999	300	10
MLC 2000W	2000 - 2099	300	10

**Note:** The coupling size range is an indication of size for ordering purposes only. Couplings are manufactured to suit customer requirements.

Also produced in Nitrile rubber and with grade 1.4401 (316) stainless steel fittings. Please contact us for availability.

