



A range of couplings especially designed for small diameter plumbing applications. Both straight and adaptor couplings are available.

These couplings are ideal for emergency repairs as they are quick and easy to install and require no special tools.

Uses

- These couplings are used to connect pipes in most low/non-pressure plumbing systems. The straight couplings are suitable for use with pipes of similar outside diameters, whereas adaptor couplings are used to join pipes of different outside diameters or materials.

STRAIGHT COUPLINGS

REFERENCE NUMBER	SIZE RANGE (mm)	WIDTH (mm)	T (mm)
MDC 32	24 - 32	65	5
MDC 40	32 - 40	65	5
MDC 50	42 - 50	65	5
MDC 65	55 - 65	90	5.7
MDC 75	65 - 75	90	6.4
MDC 89	75 - 89	100	7

ADAPTOR COUPLINGS

REFERENCE NUMBER	SIZE RANGE (mm)	WIDTH (mm)	T (mm)
MAC 0401	32 - 40	24 - 32	65
MAC 0501	40 - 50	24 - 32	65
MAC 0502	40 - 50	32 - 40	65
MAC 0632	53 - 63	32 - 40	65
MAC 0633	53 - 63	40 - 50	90
MAC 0893	75 - 89	40 - 50	100
MAC 0894	75 - 89	53 - 63	100



Mission Tees and Elbows connect to new and traditional plumbing pipes without the need for special tools thereby making them ideal for emergency replacements or repair. They are manufactured synthetic rubber with 300 series corrosion resistant stainless steel end clamps.

Their design makes them especially suitable for use in confined areas.

Uses

- Emergency repairs to existing pipework without the need for special tools.
- New connections to existing pipework.
- Replacement of existing tees or elbows when cut out for replacement or repair.

TEES

REFERENCE NUMBER	SIZE RANGE (mm)
MTY 150	41 - 48
MTY 200	54 - 63
MTY 300	80 - 89
MTY 400	105 - 116

ELBOWS

REFERENCE NUMBER	SIZE RANGE (mm)
M90L 150	41 - 48
M90L 200	54 - 63
M90L 300	80 - 89
M90L 400	105 - 116

